



www.espuk.com

EM2W NM & M EXIT SIGN

EMERGENCY LIGHTING LUMINAIRE INSTRUCTIONS AND TEST PROCEDURES

TECHNICAL PARAMETER

Batteries installed or replaced: Nicd 4.8V 600mAH
 Supply Voltage: 220-240V/50/60Hz
 Charging Current: 85-90mAH
 Charging Duration: 24 Hours
 Batteries Protection: Overcharge and full discharge
 Discharge Duration: more than 3 Hours
 Lamp Source: High Power White LED
 Max Intensity: 6100Mcd
 Operation Indicator: Charge LED
 Proration Rating: IP20
 Operation Temperature: 0 - 60 Degrees C
 Humidity: up to 95% Relative Humidity
 Dimensions: 380 x 195 x 51mm
 Weight: 1350g

Luminaire Type/Ref:

Date of Installation:

Location:

Month	Test	1st Year		2nd Year		3rd Year		4th Year		5th year	
		Sign	Date	Sign	Date	Sign	Date	Sign	Date	Sign	Date
1	Functional										
2	Functional										
3	Functional										
4	Functional										
5	Functional										
6	1 hour										
7	Functional										
8	Functional										
9	Functional										
10	Functional										
11	Functional										
12	1 Hour										
	3 Hour										

