beacon®

Technical Specification

ESP ScolmoreGROUP

Product Code: UDTAPLBMSS

Description: Stainless Steel Assistance Alarm, Power, Light and Buzzer Module

General Information

Dimensions (mm)	87 x 87 x 41
Plate Size	Single Gang
Finish	Steel Grey
Materials	Stainless Steel (Grade 304)
Mounting	Surface or Flush (Surface Back Box Not Included)
Indication	LED illuminates in red when in alarm state
Buzzer Sound Level When Activated (db)	>80
Purpose	Activation and Reset Circuits
Warranty (Years)	2

Supply & Power

Operating Voltage (V AC)	100 - 230
Maximum Cable Size (mm²)	1.5
Power Consumption (A)	0.2
Battery Backup	A23 Battery

Inputs

Input Type	Ground & 2 live circuits - X1 & X2
Activation Type	Energise with a Normally Open Clean Contact

Outputs

Number of Outputs	2
Output Type	1 Switched Live sharing common ground Separate output for additional sounders
Output Rating	12V 500mA

Environment

Ingress Protection	IP20

Supplied User Manual

Additional Information If mounting surface you will need UDTASMBSS Surface Mount Back Box.

Features

Built in Battery Backup with Supplied A23 Battery
Sounder Buzzes Intermittantly When Battery Needs Replacing

Accessories

UDTAPLBMSS: Stainless Steel Assistance Alarm, Power, Light and Buzzer Module
UDTALBMSS: Stainless Steel Assistance Alarm Light and Buzzer Module
UDTAPCMSS: Stainless Steel Assistance Alarm Pull Cord Module
UDTASPCSS: Stainless Steel Assistance Alarm Replacement Pull Cord
UDTAREMSS: Stainless Steel Assistance Alarm Reset Module
UDTASMBSS: Stainless Steel Surface mount Box

IP20 | BATTERY BACK-UP | UKCA | CE | 2 YEAR GUARANTEE